

# Large Format Print Solutions ideal for CAD & GIS

iPF605

you can

The **imagePROGRAF iPF605** is a 24" large format printer, ideal for printing fine lines, re-creating vivid colours and producing high quality detailed images. With a 1,200 dpi resolution, solid image consistency and high quality text reproduction this printer is perfect for the CAD/GIS market.

iPF605 <b>24</b> INCH
2,400 X 1,200DPI
5 COLOURS
A1 33 SECONDS
15,360 NOZZLES
HP GL/2 & HP RTL COMPATIBLE
BORDERLESS PRINTING



## Key Features

- Sharper, thinner lines and high black density for CAD plan production
- Great colour output with brilliant text and less abrasion
- Economy Printing Mode for lower running costs
- Superb graphics with vivid colours and solid image consistency
- Incredible print speeds – A1 in 33 seconds
- HPGL/2 and HP RTL compatibility and includes HDI Driver for CAD applications as standard
- Large LCD with graphics ensures easy operation
- High performance, high durability cutter incorporated for a professional finish
- Compact and quiet - it's the output not the noise that gets you noticed

 imagePROGRAF

**Canon**

# Specifications: iPF605

Class Ink Type Maximum Print Resolution Printing Speed (A1 Roll, Full Colour Image) Plain paper Coated Paper Photo Glossy Paper Dimensions, Weight (Net) W x D x H (mm), (kg)	24-inch Pigment and Dye reactive ink, 5 colours (MBK x 2, BK, C, M, Y) 2,400 x 1,200 dpi  0:33 (Fast-CAD) 1:19 (Standard-CAD) 2:44 (Standard-Full Colour Image)  <b>iPF605</b> 997 (W) x 670 (D) x 344 (H) mm; Weight approx. 45 kg 997 (W) x 870 (D) x 993 (H) mm; Weight approx. 60 kg  <b>iPF605</b> 1.140 (W) x 914 (D) x 645 (H) mm; Weight approx. 69 kg 1,115 (W) x 864 (D) x 237 (H) mm; Weight approx. 22 kg
Main Unit Main Unit with stand	
Main unit with palette Printer Stand	
Power Supply Input power Power consumption Standby power consumption (At the low power mode) 220 V - 240 V 100 V - 120 V Power off (standby)	AC 100 - 120 V (50/60 Hz) - AC 220 - 240V (50/60Hz) 100 W or less  6 W or less (when IEEE1394 is mounted, 11 W or less) 5 W or less (when IEEE1394 is mounted, 10 W or less) 1 W or less (In compliance with Executive Order of the President of the United States of America) Temperature: 15 - 30°C, Humidity: 10 - 80% (Condensation free)
Operational Environment Acoustic Noise Acoustic pressure	Operation: 49dB (A) or less (iPF605)/52dB (A) or less (iPF610), Standby 35dB (A) or less
Acoustic power Minimal Line Width Line Accuracy	Operation: 6.3 Bels or less (iPF605)/6.6 Bels or less (iPF610) 0.02 mm (Theoretical value) ±0.1 % or less (User adjustments necessary. Printing environment media must match that used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only.) Large LCD: 160 x 128 dots, Key x 12, LED x 5 US-English, Japanese US-English, French, German, Italian, Spanish, Chinese, Korean, Japanese (Kanji), Russian GAR0, HP-GL/2, HP RTL
Operation Panel Display Language on operation panel Displayable Language on LCD	
Printer Language Interface USB2.0 Hi-Speed Type Mode Connector type Ethernet Type Standard	Built-in Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Series B (4 pins)  Built-in IEEE 802.3 10base-T IEEE 802.3u 100base-TX / Auto-Negotiation IEEE 802.3 x Full Duplex
Protocol IEEE1394 (Option) Type Standard Data-transfer time Connector type Operating Systems supported Regulations	IPX/SPX (Netware 4.2(J), 5.0(J), 6.0(J)) SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk  Slot card type IEEE1394 - 1995, P1394a, Half duplex, Data/Strb differential serial 100 / 200 / 400 Mbit/sec. In compliance with IEEE1394 - 1995, 6 pins, No power supply Windows 2000, XP, Server 2003, Vista / Macintosh OS 9, OS X CE Mark, CB Certification, TUV (GS), Gost-R, UL, FCC class B
<b>PRINT HEAD</b> Model Type Head configuration Nozzle pitch Nozzle per chip Droplet size	PF-03 Bubble-jet on demand 6 colours integrated type (6 chips per print head) 1,200 dpi x 2 MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each 4 pl per colour

<b>INK TANK</b> Model	PFI-102 (130 ml) MBK, BK, C, M, Y
<b>MEDIA HANDLING</b> Roll paper Cut sheet Cut Sheet (Cassette - iPF610 only) Media type Roll paper	Top-loading, front output (front feeding, front output for thick media) Front-loading, Front Output  Front loading, front output  Standard Paper 80 gsm, Standard Paper 90 gsm, Matt Coated Paper 90 gsm, Glossy Photo Quality Paper 190 gsm / 240 gsm / 300 gsm, Satin Photo Quality Paper 190 gsm / 240 gsm / 300 gsm, Photo Realistic Paper 210 gsm, Pearl Photo Paper 260 gsm, Matt Coated Paper 120 gsm / 140 gsm / 180 gsm, Opaque White Paper 120 gsm, High Resolution Self-adhesive Graphic Paper 140 gsm, High Resolution Barrier Paper 180 gsm, Glossy Proofing Paper 195 gsm, Semi-Glossy Proofing Paper 195 gsm / 255 gsm.
Media Size Roll paper (width)	ISO: A3, A2, A1, JIS: B4, B2, ARCH: D 24" Others: 8", 10", 14", 16", 17", 300 mm, A3+ (329 mm)
Cut Sheet	ISO: A4, A3, A3+, A2, A1, B4, B3, B2, DIN: C4, C3, C2, JIS: B4, B3, B2, ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34", ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15", 16 x 20" (US Photo size), Poster: 20 x 30", 300 x 900 mm, Others: 13 x 22", 17 x 24"
Cut Sheet (Cassette) (Cassette - iPF610 only)	ISO: A4, A3, A3+, A2; JIS: B4, B3; ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22"; ARCH: 12 x 18"; Photo: 14 x 17", 12 x 16", 10 x 12", 10 x 15", 8 x 10", 16 x 20" (US Photo size); Others: 13 x 22"
Media Thickness Maximum Outside Diameter of Roll Paper Media Core Size Media Width	Roll paper & Cut sheet: 0.07 - 0.8 mm  150.0 mm Internal diameter of roll core: 2" / 3" (Option) Roll paper: 203 - 610 mm Cut sheet: 203 - 610 mm
Minimal Printable Paper Length Maximum Printable Paper Length	203 mm  Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m
Margins (Top, Bottom, Sides) Recommended area	Roll paper: Top: 20 mm, Bottom: 5 mm, Side: 7 mm Cut Sheet (Top loading/Cassette): Top: 20 mm, Bottom: 27 mm, Side: 5 mm Cut Sheet (Front Loading) Top: 20 mm, Bottom: 23 mm, Side: 5 mm Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless print): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut Sheet (Front loading) Top: 3 mm, Bottom: 23 mm, Side: 3 mm Cut Sheet (Top loading/Cassette): Top: 3 mm, Bottom: 3 mm, Side: 3 mm
Printable area	10" (254 mm), B4 (257 mm), A3+ (329 mm), 14" (356 mm), 16" (407 mm), A2 (420 mm), A2+/17" (432 mm), B2 (515 mm), A1 (594 mm), 24" (610 mm)
Media width for borderless printing	
<b>OPTION</b> Printer Stand Roll Holder Set IEEE1394 Expansion Board	ST-24 RH2 - 24 (2-inch core spindle with 3-inch media tube attachment and borderless printing space) EB-05
<b>CONSUMABLES</b> Ink Tank Print Head Maintenance Cartridge	PFI-102 (130 ml) ; MBK, BK, C, M, Y PF-03 MC-16

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

English Edition  
© Canon Europa N.V., 2011

Canon (UK) Ltd  
Woodhatch  
Reigate, Surrey  
RH2 8BF

Tel: 01737 220000  
Fax: 01737 220022  
www.canon.co.uk

Canon Ireland  
Arena Road, Sandyford  
Industrial Estate  
Dublin 18, Ireland

Tel: 01 2052400  
Fax: 01 2958141  
www.canon.ie