Large Format Print Solutions ideal for CAD & GIS

iPF750 / iPF755

you can

The imagePROGRAF iPF750 and iPF755 are 36"/A0 printers, delivering class leading productivity, exceptional quality, accuracy and an advanced set of features to ensure an excellent return on investment.

iPF750 / iPF755 **36** INCH

> 2,400 X 1,200DPI

ECONOMY PRINTING MODE

5 COLOURS

A0 48 SECONDS

> 15,360 NO77LFS

160GB HDD (iPF755)

BORDERLESS PRINTING



Key Features

- Manage costs and track ROI Full accounting and eMaintenance software included.
- Space saving Unique compact design to fit anywhere.
- User Friendly Simple roll paper loading system and control the printer from the front.
- Maximise productivity -"Hot Swap" ink tanks, changeable during production
- Minimise printer downtime with media mismatch detection (iPF755).
- High capacity basket with stacking functionality to prevent damage to prints.
- Highly accurate with 0.02mm minimum line width and +/-0.1% line accuracy.
- Integrate with your office applications with Microsoft Office Plug-in.
- HP-GL/2 and HP-RTL Compatible: -
 - Capable of handling large vector files
 - HP-GL/2 pallet and pen settings
 - HP-GL/2 and HP-RTL nesting (iPF755).
 - HP-GL/2 auto-rotation.





Specifications: iPF750 / iPF755

/	
Class	36-inch
Ink Type	Dye and pigment reactive ink: BK, MBK x 2, C, M, Y
Maximum Print Resolution	2,400 x 1,200 dpi
Printing Speed	_, -, · · · · · · · , <u>- · · · · · · · · · · · · · · · · · · </u>
(A0 Roll, Full Colour Image)	
Plain Paper	0.48 (Draft mode)
	1.14 (Standard Mode)
Coated Paper	1.14 (Draft Mode)
	2.26 (Standard Mode)
	3.51 (High Quality Mode)
Dimensions, Weight (Net)	<u></u>
W x D x H (mm), (kg)	iPF750: Main unit with a basket open and a printer stand
	1,304(W) x 870(D) x 1,062(H)mm; Weight: approx. 62.9kg
	iPF755: Main unit with a basket open and a printer stand 1,304(W) x 870(D) x 1,062(H)mm; Weight: approx. 63.1kg
Dimensions, Weight	1,304(VV) X 870(D) X 1,002(11)111111, VVelgili. applox. 03.1kg
(Packaged)	
W x D x H (mm), (kg)	iPF750: Main unit 1,434(W) x 830(D) x 770(H)mm;
,,,,,,,	Weight: approx. 75.1kg
	iPF755: Main unit 1,434(W) x 830(D) x 770(H)mm;
	Weight: approx. 75.3kg
	iPF750: Stand and Basket 1,380(W) x 760(D) x 240(H)mm;
	Weight: approx. 16.8kg
	iPF755: Stand and Basket 1,380(W) x 760(D) x 240(H)mm;
	Weight: approx. 16.8kg
Power Supply	AC 100 3/0 V (FO (CO LI=)
Input power Power consumption	AC 100 - 240 V (50/60 Hz) 140W or less
Standby power consumption	14077 01 1633
(At the low power mode)	
100 V - 120 V	5W or less
220 V - 240V	6W or less
Power off (standby)	1W or less (In compliance with Executive Order of the President
	of the United States of America)
Operational Environment	Temperature: 15 - 30°C, Humidity: 10 - 80% (Condensation free)
Acoustic Noise	Operation: FO dB (A) or loss Standby: 7F dB (A) or loss
Acoustic pressure Acoustic power	Operation: 50 dB (A) or less, Standby: 35 dB (A) or less Operation: 6.6 Bels or less
Minimal Line Width	0.02mm (Theoretical value)
Line Accuracy	±0.1 % or less (User adjustments necessary. Printing environment
Enter recuracy	media must match that used for the adjustments. CAD paper
	required: Plain paper, CAD tracing paper, coated paper,
	CAD translucent matte film only.)
Operation Panel Display Large	LCD: 160 x 128 dots, Key x 13, LED x 5
Language on operation panel	US-English, Japanese
Displayable Language on LCD	US-English, French, German, Italian, Spanish, Chinese (simplified)
51	Korean, Japanese (Kanji), Russian
Printer Language	GARO, HP-GL/2, HP RTL
Interface USB	
Type	Built-in
Mode	Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer
Connector type	Series B (4 pins)
Ethernet	
Туре	Built-in
Standard	IEEE 802.3 10base-T
	IEEE 802.3u 100base-TX / Auto-Negotiation
	IEEE 802.3ab 100base-T / Auto-Negotiation
	IEEE 802.3 x Full Duplex
Protocol	IPX/SPX (Netware 4.2(J), 5.1(J), 6.0(J))
Operating Systems Supported	SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk
Windows	2000 (32)/XP (32 & 64)/Server 2003 (32 & 64)/Server 2008
VVIIIdows	(32 & 64)/Vista (32 & 64)
Macintosh	OS X (32 & 64)
Memory	
Standard Memory	256Mb
HDD	iPF755 - 160Gb (including 8Gb Dynamic Memory)
PRINT HEAD	
Model	PF-04
Туре	Bubble-jet on demand
Head configuration	6 colours integrated type (6 chips per print head x 1 print head)
Nozzle pitch	1,200dpi
Nozzle per chip	MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each
Droplet size Head replacement	4 pl per colour User replacement
. I I COU I EDIACEITIEI I	ODG TOPICCITICITE

INK TANK Model	PFI-102 (130ml): MBK/BK/C/Y, PFI-104 (130ml): M	
MEDIA HANDLING Roll paper Cut sheet Media type	One roll, top-loading, front output Top-feeding, front output (Manual feed using media locking lever)	
Roll paper	Standard Paper 80gsm Standard Paper 90gsm Matt Coated Paper 90gsm Matt Coated Paper 90gsm Glossy Photo Quality Paper 190gsm / 240gsm / 300gsm Satin Photo Quality Paper 190gsm / 240gsm / 300gsm Pearl Photo Paper 260gsm Matt Coated Paper 120gsm / 140gsm / 180gsm Opaque White Paper 120gsm High Resolution Self-adhesive Graphic Paper 140gsm High Resolution Barrier Paper 180gsm Glossy Proofing Paper 195gsm Semi-Glossy Proofing Paper 195gsm / 255gsm	
Media Size Roll paper (width)	ISO: A3, A2, A2+, A1, A0, JIS: B4, B2, B1, ARCH: 24", 30", 36" Others: 10", 14", 16", 17", Banner (300mm)	
Cut sheet	ISO: A4, A3, A3+, A2, A2+, A1, A0, B4, B3, B2, B1 DIN: C4, C3, C2, C1, C0 JIS: B4, B3, B2, B1, B0 ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34",	
	28 x 40", 34 x 44" ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48" Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15" 16 x 20" (US Photo size), Poster: 20 x 30", 30 x 40", 300 x 900mm,	
Media Thickness	Others: 13 x 22" Roll paper & Cut sheet: 0.07 - 0.8mm	
Maximum Outside Diameter of Roll Paper Media Core Size Media Width	150.0mm Internal diameter of roll core: 2" / 3" Roll paper: 254 (10") – 914.4 (36")mm Cut sheet: 203.2 (8") – 917 (DIN CO)mm	
Minimum regular format size (Vertical)	Roll paper: 203.2mm (8")	
Maximum Printable Paper Length	Cut Sheet: 279.4mm (11"): Letter size (long side) Roll paper: 18m (Varies according to the OS and application) Cut sheet: 1.6m (Varies according to the OS and application)	
Margins (Top, Bottom, Sides) Recommended area	Roll paper: Top: 20mm, Bottom: 5mm, Side: 5mm	
Printable area	Cut sheet: Top: 20mm, Bottom: 23mm, Side: 5mm Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless print): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet: Top: 3mm, Bottom: 23mm, Side: 3mm	
Media width for borderless printing	10"(254mm), B4(257mm), A3(297mm), Banner(300mm), 14"(356mm), A2(420mm), A2+17"(432mm), B2(515mm) A1(594mm), 24"(610mm), B1 (728mm), A0(841mm), 36" (914mm)	
OPTION Roll Holder Set (for both 2" and 3" core roll media)	RH2-33	
CONSUMABLES Ink Tank Print Head Maintenance Cartridge	PFI-102 (130ml): MBK/BK/C/Y, PFI-104 (130ml): M PF-04 MC-10	
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods.		

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice.™ and Θ: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.













Canon Europe

Uxbridge, Middlesex UB11 1ET UK



Head replacement

User replacement

canon-europe.com

English Edition © Canon Europa N.V., 2011

Canon Europe Ltd 3 The Square, Stockley Park